

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A device, comprising:

a substrate having a cavity extending ~~from at least one~~ into a surface of the substrate;

a cathode having an electron-emitting coating disposed thereon, wherein the cathode is suspended near the opening of the cavity in the substrate, wherein the cathode and the cavity are configured to form an air gap between the substrate and the cathode for providing a thermal barrier around the cathode;

an anode constructed of an electrically conductive material, wherein the anode is configured to receive electrons emitted by the cathode, and wherein the anode is configured to produce an electrical current from the received electrons, wherein the anode is configured to communicate the electrical current to an external circuit;

a grid forming at least one aperture configured for allowing the passage of electrons therethrough, wherein the grid is constructed of an electrically conductive material, and wherein the grid is positioned between the cathode and anode;

a seal for creating a controlled environment in an area surrounding the anode, cathode, and grid; and

a circuit configured for heating the cathode.

2. (Original) The device of Claim 1, further comprising, at least one control circuit for selectively supplying a voltage to the grid to control the magnitude of the flow of electrons through the aperture of the grid, thereby controlling the electrical current received by the anode.

3. (Original) The device of Claim 1, wherein the grid comprises a plurality of elongated conductive strips, wherein the plurality of elongated conductive strips are substantially parallel to one another, and wherein the aperture of the grid is formed by the spacing between the plurality of elongated conductive strips.

LAW OFFICES OF  
CHRISTENSEN O'CONNOR JOHNSON KINDNESS  
1420 Fifth Avenue  
Suite 2800  
Seattle, Washington 98101  
206 682 8100

4. (Original) The device of Claim 3, wherein the plurality of elongated conductive strips are mounted on a raised support formed on the substrate.

5. (Original) The device of Claim 4, wherein the raised support is formed by a stacked structure.

6. (Original) The device of Claim 1, wherein the cathode is affixed to the substrate at opposite ends of the cathode, and wherein a substantial portion of the cathode is suspended over the cavity of the substrate, thereby forming an air gap between the cathode and substrate.

7. (Original) The device of Claim 1, wherein the electron emitting coating is made of a low work function material.

8. (Original) The device of Claim 1, wherein the electron emitting coating is made of a BaSrCa tricarbonat.

9. (Original) The device of Claim 1, wherein the electron emitting coating includes BaSr.

10. (Original) The device of Claim 1, wherein the electron emitting coating includes BaSrAl.

11. (Original) The device of Claim 1, wherein the electron emitting coating includes thoriated tungsten.

12. (Original) The device of Claim 1, wherein the electron emitting coating includes scandia.

13. (Original) The device of Claim 1, wherein the electron emitting coating includes scandate.

14. (Original) The device of Claim 1, wherein the electron emitting coating includes cesium.

LAW OFFICES OF  
CHRISTENSEN O'CONNOR JOHNSON KINDNESS<sup>TM</sup>  
1420 Fifth Avenue  
Suite 2800  
Seattle, Washington 98101  
206.682.8100

15. (Original) The device of Claim 1, wherein the grid is made of material selected from the group consisting of tungsten, gold, nickel, carbon, silver, and copper.

16. (Original) The device of Claim 1, wherein the grid is made of material selected from the group consisting of molybdenum and tantalum.

17. (Original) The device of Claim 1, wherein the grid contains a carbon-containing material.

18. (Original) The device of Claim 1, wherein the grid contains a silicide.

19. (Original) The device of Claim 1, wherein the controlled environment surrounding the grid, cathode, and anode has a vacuum drawn therein.

20. (Original) The device of Claim 1, wherein the controlled environment is an enclosed area filled with a gas selected from the group consisting of hydrogen, helium, krypton, argon, and mercury.

21. (Currently amended) A device, comprising:

a substrate having a cavity extending ~~from at least one~~ into a surface of the substrate;

a first member having an electron-emitting coating disposed on the first member, wherein the first member is suspended near the opening of the cavity in the substrate;

a second member constructed of an electrically conductive material, wherein the second member is configured to receive electrons emitted by the first member, and wherein the second member is configured to produce an electrical current for an external circuit from the received electrons;

a first grid forming at least one aperture configured for allowing the passage of electrons therethrough, wherein the first grid is constructed of an electrically conductive material, wherein the first grid is positioned between the first and second member;

LAW OFFICES OF  
CHRISTENSEN O'CONNOR JOHNSON KINDNESS"  
1420 Fifth Avenue  
Suite 2800  
Seattle, Washington 98101  
206.682.8100

a second grid forming at least one aperture configured for allowing the passage of electrons therethrough, wherein the second grid is constructed of an electrically conductive material, wherein the second grid is positioned between the first and second member;

a seal for creating a controlled environment in an area surrounding the first and second grid and the first and second member; and

a circuit configured for heating the first member.

22. (Original) The device of Claim 21, further comprising, at least one control circuit for selectively supplying a voltage to the first and second grid to control the magnitude of the flow of electrons through the aperture of the grid, thereby controlling the electrical current received by the second member.

23. (Original) The device of Claim 21, wherein the aperture of the first and second grids are aligned.

24. (Original) The device of Claim 21, wherein the second grid is electrically connected to a ground source.

25. (Original) The device of Claim 21, wherein the each elongated conductive strip is mounted on a raised support formed on the substrate.

26. (Original) The device of Claim 21, wherein the first member is affixed to the substrate at opposite ends of the first member, and wherein a substantial portion of the first member is suspended over the cavity of the substrate, thereby forming an air gap between the first member and substrate.

27. (Original) The device of Claim 21, wherein the first and second grids are made of material selected from the group consisting of tungsten, gold, and tantalum.

LAW OFFICES OF  
CHRISTENSEN O'CONNOR JOHNSON KINDNESS<sup>PC</sup>  
1420 Fifth Avenue  
Suite 2800  
Seattle, Washington 98101  
206 682 8100

28. (Original) The device of Claim 21, wherein the controlled environment is an enclosed area surrounding the grid, cathode, and anode, wherein the enclosed area has a vacuum drawn therein.

29. (Original) The device of Claim 21, wherein the controlled environment is an enclosed area filled with a gas selected from the group consisting of hydrogen, helium, argon, and mercury.

30. (Currently amended) A device, comprising:

a substrate having a cavity extending ~~from at least one~~ into a surface of the substrate;

a first member having an electron-emitting coating disposed on the first member, wherein the first member is suspended near the opening of the cavity in or above the substrate;

a second member constructed of an electrically conductive material, wherein the second member is configured to receive electrons emitted by the first member, and wherein the second member is configured to produce an electrical current for an external circuit from the received electrons;

a first grid forming at least one aperture configured for allowing the passage of electrons therethrough, wherein the first grid is constructed of an electrically conductive material, wherein the first grid is positioned between the first and second member;

a second grid forming at least one aperture configured for allowing the passage of electrons therethrough, wherein the second grid is constructed of an electrically conductive material, wherein the second grid is positioned between the first and second member;

a third grid forming at least one aperture configured for allowing the passage of electrons therethrough, wherein the second grid is constructed of an electrically conductive material, wherein the third grid is positioned between the first and second member;

LAW OFFICES OF  
CHRISTENSEN O'CONNOR JOHNSON KINDNESS<sup>PC</sup>  
1420 Fifth Avenue  
Suite 2800  
Seattle, Washington 98101  
206.682.8100

a seal for creating a controlled environment in an area surrounding the first, second, and third grid, and the first and second member; and

a circuit configured for heating the first member.

31. (Original) The device of Claim 30, further comprising, at least one control circuit for selectively supplying a voltage to the first, second and third grid to control the magnitude of the flow of electrons through the aperture of the grid, thereby controlling the electrical current received by the second member.

32. (Original) The device of Claim 30, wherein the aperture of the first and second grids are aligned.

33. (Original) The device of Claim 30, wherein the second grid is electrically connected to a ground source.

34. (Original) The device of Claim 30, wherein the each elongated conductive strip is mounted on a raised support formed on the substrate.

35. (Original) The device of Claim 30, wherein the first member is affixed to the substrate at opposite ends of the first member, and wherein a substantial portion of the first member is suspended over the cavity of the substrate, thereby forming an air gap between the first member and substrate.

36. (Original) The device of Claim 30, wherein the first and second grids are made of material selected from the group consisting of tungsten, gold, and tantalum.

37. (Original) The device of Claim 30, wherein the controlled environment is an enclosed area surrounding the grid, cathode, and anode, wherein the enclosed area has a vacuum drawn therein.

LAW OFFICES OF  
CHRISTENSEN O'CONNOR JOHNSON KINDNESS"  
1420 Fifth Avenue  
Suite 2800  
Seattle, Washington 98101  
206.682.8100

38. (Original) The device of Claim 30, wherein the controlled environment is an enclosed area filled with a gas selected from the group consisting of hydrogen, helium, argon, and mercury.

39. (Currently amended) A device, comprising:

a substrate having a cavity extending ~~from~~ into at least one surface of the substrate;

a first member having electron emitting properties, wherein the first member is suspended near the opening of the cavity of the substrate, wherein the first member and the cavity are configured to form an air gap between the substrate and the first member for providing a thermal barrier around the first member;

a second member constructed of an electrically conductive material, wherein the second member is positioned over the cavity of the substrate, wherein the second member is configured to receive electrons emitted by the first member, and wherein the second member is configured to produce an electrical current to an external source from the received electrons;

a seal for creating a controlled environment in an area surrounding the first and second member; and

a circuit configured for heating the first member.

40. (Original) The device of Claim 39, wherein the controlled environment is an enclosed area surrounding the ~~cathode~~ first member and anode, wherein the enclosed area has a vacuum drawn therein.

41. (Original) The device of Claim 39, wherein the controlled environment is an enclosed area filled with a gas selected from the group consisting of hydrogen, helium, argon, and mercury.

42 - 43. (Canceled)

44. (Original) A device, comprising:

LAW OFFICES OF  
CHRISTENSEN O'CONNOR JOHNSON KINDNESS\*  
1420 Fifth Avenue  
Suite 2800  
Seattle, Washington 98101  
206.682.8100

a substrate means having a cavity that extends into the substrate;

a cathode means having an electron-emitting coating disposed thereon, wherein the cathode means is suspended near the opening of the cavity in the substrate, wherein the cathode means and the cavity are configured to form an air gap between the substrate means and the cathode means for providing a thermal barrier around the cathode means;

*end*  
an anode means constructed of an electrically conductive material, wherein the anode means is configured to receive electrons emitted by the cathode means, and wherein the anode means is configured to produce an electrical current from the received electrons, wherein the anode means is configured to communicate the electrical current to an external circuit;

a grid means forming at least one aperture configured for allowing the passage of electrons therethrough, wherein the grid means is constructed of an electrically conductive material, and wherein the grid means is positioned between the anode means and cathode means;

a seal for creating a controlled environment in an area surrounding the anode means, cathode means, and grid means; and

a circuit configured for heating the cathode means.

45. (Original) The device of Claim 44, further comprising, at least one control circuit for selectively supplying a voltage to the grid means to control the magnitude of the flow of electrons through the aperture of the grid means, thereby controlling the electrical current received by the anode means.

LAW OFFICES OF  
CHRISTENSEN O'CONNOR JOHNSON KINDNESS<sup>PC</sup>  
1420 Fifth Avenue  
Suite 2800  
Seattle, Washington 98101  
206.682.8100